

SAFETY DATA SHEET

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 04-15-2015

Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

Product Name: Elite Chemical Resistant Urethane Coating (Colors) **PART A**
Product Codes: Series No. 8142-0400
Recommended Use: Concrete Coating.
Sold By: Gabriel First Corp.
Street Address: 233 West Commercial Street
City, State, Zip: East Rochester, NY 14445-0191
Telephone: 585-381-7000
Emergency Phone: 800-424-9300
Date Revised: 04-15-15
Chemical Name or Class: Polyester Polyol Solution

Section 2 – Hazards Identification**Hazard Overview****GHS Classification:**

Flammable Liquid: Category 3
Specific Target Organ Toxicity – Single Exposure: Category 3
Acute Oral Toxicity: Category 4
Skin Corrosion/Irritation: Category 2
Serious Eye Irritation: Category 2A
Acute Toxicity Inhalation: Category 4
Acute Toxicity Skin: Category 4
Specific Target Organ Toxicity Repeated Exposure: Category 2
Acute Hazard to Aquatic Environment: Category 3

GHS Label Elements and Precautionary Statements**Label Elements:****Hazard Statements:**

Warning: Flammable liquid and vapor.
Warning: May cause respiratory irritation.
Warning: Harmful if swallowed.
Warning: Causes skin irritation.
Warning: Causes serious eye irritation.
Warning: Harmful if inhaled.
Warning: Harmful in contact with skin.
Warning: May cause damage to organs (auditory system) through prolonged or repeated exposure. Harmful to aquatic life.

Precautionary Statements:

P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P260 Do not breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Response:	<p>P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.</p> <p>P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical, water fog for extinction.</p> <p>P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.</p> <p>P312 If Inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.</p> <p>P301 + P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.</p> <p>P330 Rinse mouth.</p> <p>P302 + P352 IF ON SKIN: wash with plenty of soap and water.</p> <p>P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.</p> <p>P362 + P364 Take off contaminated clothing and wash it before reuse.</p> <p>P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P337 + P313 IF eye irritation persists: Get medical advice/attention.</p> <p>P314 Get medical advice/attention if you feel unwell.</p>
Storage:	<p>P403 + P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P233 Keep container tightly closed.</p>
Disposal:	<p>P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.</p>
Other Non-Classifiable Potential Hazards:	<p>Carcinogenicity Category 2, (Ethyl benzene at less than 17% in a study done by the NTP was determined to not be carcinogenic).</p>

HMIS Hazard Classification

Health: 2 Flammability: 3 Reactivity: 0 Personal Protective Equipment: G

Potential Health Effects

Eyes:	May cause corneal damage if left untreated which is slow to heal but usually reversible.
Skin:	May cause irritation or allergic response. May cause defatting, dryness, cracking, rash or redness or dermatitis.
Skin Absorption:	Solvents can penetrate the skin causing effects similar to those for acute inhalation symptoms.
Ingestion:	Can cause irritation to the digestive tract including sore throat, abdominal pain, nausea, vomiting and diarrhea. Vomiting may cause Aspiration of solvents resulting in chemical pneumonitis.
Inhalation Health Risks and Symptoms of Exposure:	Solvent vapors are irritating to the eyes, nose and throat and respiratory tract resulting in dryness of the throat and tightness in the chest. Other symptoms include headache, nausea, narcosis, fatigue and loss of appetite.

Health Hazards (Acute and Chronic): Chronic Exposure to organic solvents has been associated with various neurotoxic effects including brain damage, nervous system damage or death. Prolonged vapor contact may cause conjunctivitis. Chronic inhalation may also include loss of memory, loss of intellectual ability and loss of coordination. Corneal damage is possible but usually reversible. Repeated Exposure to solvents can cause anemia, liver abnormalities, kidney damage or cardiac abnormalities.

Medical Conditions Generally Aggravated by Exposure: Respiratory conditions or other allergic response.

Carcinogenicity: **OSHA:** No **NTP:** No **IARC:** Yes

Additional Carcinogenicity Information:

May Contain Ethyl Benzene (IARC possible carcinogen). Titanium Dioxide is listed by IARC as possibly carcinogenic to humans (Group 2B). Some colors may contain carbon black - Explanation Of Carcinogenicity for carbon: IARC MONOGRAPHS ON EVALUATION OF CARCINOGENIC RISK OF CHEMICALS TO MAN, VOL 65, PG 149, 1996: GROUP 2B.

Section 3 – Composition/Information on Ingredients

Ingredient	CAS No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Propylene Glycol Monomethyl Ether Acetate	108-65-6	50ppm	None	None	3-7
Saturated Polyester Polyol (Non-Hazardous)	Unknown	None	None	None	15-40
POLYESTER POLYOL	NJTSRNS0001C	None	None	None	10-30
Siloxanes And Silicones, Di-Me Reactions Products With Silica (Non-Hazardous)	67762-90-7	None	None	None	0.1-1
Siloxanes and Silicones, Di-Methyl (Non-Hazardous)	63148-62-9	None	None	None	0.1-1
*Xylene	1330-20-7	100 ppm	100 ppm	150 ppm	8
2,6-Dimethyl-4-Heptanone	108-83-8	25 ppm	25 ppm	None	0.1-1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ingredient	CAS No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
*Ethyl Benzene	100-41-4	100 ppm	100 ppm	125 ppm	<0.5
Polyalkylene Glycol	9038-95-3	None	None	None	0.1-1
4,6-Dimethyl-2-Heptanone	19549-80-5	None	None	None	0.1-1
Dibutyltin Dilurate	77-58-7	0.1mg / m3	0.1mg / m3	0.1mg / m3	0.1-1
Cellulose Acetate Butyrate	9004-36-8	None	None	None	0.1-1
Methyl N-Amyl Ketone	110-43-0	100 ppm	50 ppm	None	7-13
Ethyl 3-Ethoxypropionate	763-69-9	None	None	None	3-7
Additive	NJTSRN 800963-5023	None	None	None	0.1-1
Colors May Contain @ 10-30%:					
Titanium Dioxide	13463-67-7	10mg/m3	10mg/m3	5mg/m3	
*CARBON	1333-86-4	3.5 ppm	3.4 ppm	None	<1.0
Acrylic Polymers (Non-Hazardous)	Trade Secret	None	None	None	
C.I. Pigment Violet 19	1047-16-1	None	None	None	
Barium Sulfate	7727-43-7	5 mg/m3	10 mg/m3	None	
Zinc Salt of Alkyl Naphalene Sulfonic Acid	Undisclosed	None	None	None	
Solvent Naptha	64742-88-7	None	None	None	
Polyamine Polyester Polymer	(Non Hazardous)	None	None	None	
C.I. Pigment Blue 15	147-14-8	None	None	None	
C.I. Pigment Blue	25869-00-5	None	None	None	
C11-C13 Isoparaffin	64741-65-7	None	None	None	
C.I. Pigment Green 17	1308-38-9	None	None	None	
Alkyl Polyether Phosphate Ester	Trade Secret	None	None	None	
C.I. Pigment Green 7	1328-53-6	None	None	None	
C.I. Pigment Green 36	14302-13-7	None	None	None	
C.I. Pigment Yellow	4531-49-1	None	None	None	
C.I. Pigment Yellow	5567-15-7	None	None	None	
C.I. Pigment Yellow 42	51274-00-1	None	None	None	
Pigment Orange	15793-73-4	None	None	None	
C.I. Pigment Red 101	1309-37-1	None	None	None	
C.I. Pigment Red 3	2425-85-6	None	None	None	
Aluminum Silicate Dehydrate	1332-58-7	None	None	None	
Mineral Spirits	8052-41-3	100 ppm	100 ppm	None	
C.I. Pigment Red 187	59487-23-9	None	None	None	

SECTION 3 NOTES:

*Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372. All components are on the TSCA list. Xylene Stel= 150PPM (ACGIH) Methyl N-Amyl Ketone Stel (ACGIH)= 100PPM. Ethyl 3-Ethoxypropionate: USA country specific exposure limits have not been established or are not applicable. Chemical company exposure limit (TLV) 50ppm and (STEL) 100ppm are recommended. Canada, Ontario OEL (Ministry of Labor – Control of Exposure) TWA 50ppm.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

Section 4 – First Aid Measures

Eyes:	Flush eyes with water for at least fifteen minutes and consult a physician.
Skin:	Wash affected area with soap and water and remove contaminated clothing promptly.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a physician.
Inhalation:	Remove victim to fresh air area and administer oxygen if necessary. Consult a physician if necessary.

Section 5 – Fire-Fighting Measures

Flammable Limits in Air, (% by volume): **Upper:** Not available.
Lower: Not available.

Flash Point: 100F

Method Used: Seta flash.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Extinguishing Media:	Foam, Alcohol Foam, CO ₂ , Dry Chemical, Water Fog.
Special Fire Fighting Procedures:	Do not enter confined fire area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Cool all fire exposed containers with water. Minimize contact with material.
Unusual Fire and Explosion Hazards:	Closed containers may explode when exposed to extreme heat. Solvent vapors may be heavier than air. Under conditions of stagnant air, vapors may build up and travel along the ground to an ignition source which can result in flash back to the source of the vapors. Toxic vapors could be evolved from the combustion of this material.

Section 6 – Release Measures

Steps to be Taken in Case Material is Released or Spilled:	Remove all sources of ignition and ventilate the area. Wear appropriate protective equipment such as vapor cartridge or air supplied respirator when necessary. Dike and absorb the material with absorbent such as clay and place in disposal containers.
-------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Section 7 – Handling and Storage

Precautions to be Taken in Handling and Storage:	Store in cool dry area. Seal all partially used containers. Wash with soap and water before eating, drinking, smoking or using the toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the SDS's of all the components prior to using the material. Properly label all containers.
Other Precautions:	Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles cannot be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof. Supply appropriate ventilation or engineering controls prior to using this product.

Section 8 – Exposure Controls/Personal Protection

Respiratory Protection:	Use a NIOSH approved respirator as required to prevent over-exposure to vapor in accordance with 29 CFR 1910.134. Use a positive pressure respirator when airborne concentrations are not known or if exceeding TLV's or if working in a confined space. Always consider the hazards from all components in the mixed material state.
Ventilation :	Exhaust ventilation sufficient to keep the airborne concentrations of the solvents and other hazardous materials below the toxic level concentrations.
Protective Gloves:	Impervious gloves – neoprene or rubber.
Eye Protection:	Splash goggles or glasses with side shields. If the environment warrants, a full face shield should be employed.
Other Protective Clothing or Equipment:	Wear body covering clothing and other coverings as necessary such as an apron and appropriate footwear to avoid contact.
Work Hygienic Practices:	Observe good general hygienic practices.
See Section Three for occupational exposure limit values.	

Section 9 – Physical and Chemical Properties

Appearance and Odor:	Low viscosity liquid with ketone solvent odor.
Boiling Point or Range:	279 to 375F
Vapor Density (Air = 1):	Not available.
Specific Gravity (H₂O = 1):	1.2 typical (varies by color).
Evaporation Rate:	Not available.
Solubility in Water:	Negligible.
Odor Threshold:	N/A
pH:	N/A
Melting Point/Freezing Point:	N/A
Vapor Pressure:	N/A
Auto-ignition Temperature:	N/A
Partition Coefficient: n-Octanol/water:	N/A
Decomposition Temperature:	N/A

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 10 – Stability and Reactivity

Stability:	Stable.
Conditions to Avoid (Stability):	Avoid excessive heat or open flames. This material should not be mixed with phosphorous containing material or oxidizers.
Incompatibility (Material to Avoid):	Can react vigorously with strong oxidizing agents and phosphorous containing materials.
Hazardous Decomposition or By-Products:	Carbon Monoxide and Carbon Dioxide.
Hazardous Polymerization:	Will not occur.

Section 11 – Toxicological Information

No data for the product itself.

Component Data:**Component Propylene Glycol Monomethyl Ether Acetate CAS# 108-65-6:**

LD50 Oral (rat) 8,532 mg/kg. LD50 Dermal (rabbit) >5000 mg/kg. LC0 Inhalation 6 hr (rat = 4345 ppm. Eye irritation, slightly Irritating. Dermal: non-sensitizer (guinea pig, maximization test). Repeated Dose Toxicity: 14 days, inhalation – NOAEL: 300ppm, LOAEL: 1000ppm (rat. Mutagenicity in vitro: Ames – negative (salmonella typhimurium, metabolic activation; with/without) Developmental Toxicity/Teratogenicity: Rat, female, inhalation, 6hrs/day 7 days a week; NOAEL (teratogenicity) . 4000 ppm – No Teratogenic effects observed at doses tested.

Component CAS# 9038-95-3:

Acute oral toxicity LD50 = 5370 mg/kg (rat); Acute dermal toxicity LD50 = 21000 mg/kg (rabbit); Acute inhalation toxicity LC50 = 4670 ppm (rat); Skin irritation – slight irritation (rabbit); Eye irritation – mild irritation (rabbit).

Component CAS# 108-83-6:

Acute oral toxicity LD50 = 5800 mg/kg (rat); Acute dermal toxicity LD50 = 16000 mg/kg (rabbit); Acute inhalation toxicity LC50 = 2000 ppm (rat); Skin irritation – slight irritation (rabbit); Eye irritation – mild eye irritation (rabbit).

Component Xylene:

Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Xylene may contain Ethyl Benzene. Ethyl Benzene has shown limited evidence of a carcinogenic effect.

Component Dibutyltin Dilurate CAS# 77-58-7:

ACUTE ORAL TOX (LD50,RAT) 3200.00 MG/KG. ACUTE DERMAL TOX (LD50,RABBIT) >2000 MG/KG (NO DEATHS). ACUTE INHAL TOX (LC50, RAT) >8.10 MG/L/1 HR. AMES TEST: NEG (ACTIVATED & NONACTIVATED) INDUST CHEMS SUC H AS THIS MATL W/ACUTE TOX VALUES SHOWN & WHOSE VAPS/MISTS ARE NOT LIKELY TO BE ENCOUNTERED BY HUMANS WHEN USED IN ANY REASONABLY FORESEEABLE MANNER WOULD NOT REQ TOXIC LBL ACCORD TO U.S. DOMESTIC & I NTERNATIONAL TRANSPORT REQS. IRRIT EFTS DAT: SEV IRRITANT TO EYES OF RABBIT. MOD IRRITANT TO SKIN OF RABBIT.

Component Cellulose Acetate Butyrate Ester CAS# 9004-36-8:

Oral LD-50: (Rat): > 3,200 mg/kg (highest dose tested). Dermal LD-50: (Guinea Pig): > 1,000 mg/kg (highest dose tested). Skin Corrosion: (Guinea Pig, 24 h): slight. Skin sensitization: not a sensitizer.

Component CAS# 110-43-0:

Oral LD 50 (rat): 1600 mg/kg; Oral LD50 (mouse) 730 mg/kg; Inhalation LC50 (rat) 2000-4000 ppm, 4 hr. Dermal LD50 (rabbit) 10206 mg/kg; Dermal LD50 (guinea pig) >16200 mg/kg; Skin irritation (Rabbit) – slight to moderate; Eye irritation (rabbit) slight; Skin sensitization (human) none.

Component 763-69-9:

Acute oral toxicity LD50 = 5000 mg/kg (rat); acute dermal toxicity LD50 = 10000 mg/kg (rabbit). Component is a skin irritant.

Component additive NJTSRN 800963-5023:

Acute oral toxicity: LD50 rat>8,000,000 mg/kg; skin irritation rabbit – no skin irritation

Component Titanium Dioxide:

Inhalation 4 h LC50 > 6.82 mg/l; Oral LD50 > 5000 mg/kg, rat; In February 2006, IARC listed titanium dioxide as possibly carcinogenic to humans Group 2B.

Component Carbon:

IARC lists carbon as a possible human carcinogen Category 2B. LD50 – Intravenous, mouse = 440 mg/kg.

Section 12 – Ecological Information

No data for the product itself.

Component Data:**Component Propylene Glycol Monomethyl Ether Acetate CAS# 108-65-6:**

Biodegradation: aerobic, 100%, exposure time: 8 days. Acute and Prolonged Toxicity to fish LC50: 161 mg/l (fathead minnow), 96 hr. Acute Toxicity to Aquatic Invertebrates: EC50: 408 mg/l (water flea), 48 hr.

Component Xylene:

Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 <10mg/l, Algae: Toxic 1 < LC/EC/IC50 <10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidises rapidly by photo-chemical reactions in air.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component CAS# 110-43-0:

BOD-5: 1770 mg/kg; BOD-20: 2000 mg/kg; COD: 2420 mg/kg. Acute Aquatic Effects: 96 hr LC50 (fathead minnow) 131 mg/l and 48 hr EC50 (daphnia) >90 mg/l (highest concentration tested).

Component 763-69-9:

Possibly hazardous short term degradation products are not likely, however long term degradation products may arise. The product itself and its products of degradation are not toxic.

Component Titanium Dioxide:

Pimephales promelas (fathead minnow) < 1000 mg/l @ 96h LC50; Pseudokirchneriella subcapitata (green algae) 61 mg/l @ 72h EC50; Daphnia magna (water flea) > 1000 mg/l @ 48h EC50.

Section 13 – Waste Disposal**Waste Disposal Method:**

Dispose of the material in a waste disposal site in accordance with local, state, and federal laws. Empty containers should be handled with care due to product residue and possible vapor from organic solvents. Never use a gas or electric torch to cut the drums.

Section 14 – Transport Information**DOT:**

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ETHYL BENZENE), 3, PG III.

IMO/IMDG:

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, ETHYL BENZENE), 3, PG III.

Section 15 – Regulatory Information

No data for the product itself.

Component Data:**Component Saturated Polyester Polyol (non-hazardous):**

Europe Inventory: Component is listed or exempted. Canada Inventory: Component is listed or exempted. Canadian NPRI not required. United States Inventory: Component is listed (TSCA 8b) or exempted.

Component Propylene Glycol Monomethyl Ether Acetate CAS# 108-65-6:

Listed on TSCA and DSL Component listed on the Pennsylvania, New Jersey and Massachusetts Right to Know lists.

Component Siloxanes and Silicones, di-Me reactions products with silica:

Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component Siloxanes and Silicones, Di-Methyl:

Included on TSCA, EINECS, MITI, ACOIN, and Canadian DSL inventory or lists.

Component CAS# 108-83-6:

Pennsylvania, Massachusetts and New Jersey Right to Know, (On TSCA, DSL lists).

Component CAS# 9038-95-3:

Pennsylvania and New Jersey Right to Know (On TSCA, DSL Lists).

Component Xylene:

Xylene contains EPCRA Section 313 chemicals subject to the reporting requirements of the emergency planning and community Right to Know act of 1968. (Maximum wt % for components of Xylene are: M-Xylene CAS# 108-38-3 is 46%, P-Xylene CAS# 106-42-3 is 20%, Ethyl Benzene CAS# 100-41-4 is 19%, O-Xylene CAS# 95-47-6 is 16%). Xylene and its components are on the California Proposition 65 list for developmental toxicity, Reproductive toxicity and carcinogen list. Ingredients are on the TSCA list, DSL Canada, AICS, China, EINECS, ENCS, Korea, New Zealand, Phillipines inventory lists and on the Massachusetts, New Jersey, Pennsylvania Right to Know lists. Ethyl Benzene a component of Xylene has been designated by IARC as a possible carcinogen to humans based on increased tumor incidence in laboratory animals. Risk phrases R10 Flammable R20/21 Harmful by inhalation and in contact with skin, R38 irritating to skin, S25 Avoid contact with eyes.

Component Dibutyltin Dilurate CAS# 77-58-7:

Sara Title III Information: TOXIC SUBSTANCES CONTROL ACT (TSCA): ALL COMPONENTS ARE INCL IN EPA TOXIC SUBSTANCES CTL ACT (TSCA) CHEM SUBSTANCE INVENTORY. OSHA HAZARD COMMUNICATION STD (29CFR1910.1200) HAZARD CLASS(ES): IRRITANT. KIDNEY TOXIN. EPA SARA TITLE III SECTION 312 (40CFR370) HAZARD CLASS. IMMEDIATE HEALTH HAZARD. EPA SARA TITLE III 313 (40CFR372) TOXIC CHEMICALS "DE MINIMIS" LEVEL ARE NONE. Federal Regulatory Information: CANADA DSL-INCL ON INVENTORY. HAZARD CLASSIFICATION-CLASS D DIVISION 2B.(EEC). EINECS /ELINCS MASTER INVENTORY-INCLUDED ON INVENTORY. EEC SYMBOL-HARMFUL (XN). EEC RISK (R) PHRASES-IRRITATING TO EYES & SKIN (R36/38). HARMFUL BY INHAL (R20). EEC SFTY PHRASES-IN CASE OF CONT W/EYES, RINSE IMMEDIATE W/PLENTY OF WATER & SEEK MED ADVICE (S26). AUSTRALIA-AICS-INCLUDED ON INVENTORY. State Regulatory Information: STATE REGS: PROPOSITION 65 SUBSTANCES (COMPONENT(S) KNOWN TO STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE TOXICITY & SUBJECT TO WARNING & DISCHARGE REQUIREMENTS UNDER "SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986"): NONE.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component Cellulose Acetate Butyrate Ester CAS# 9004-36-8:

WHMIS (Canada) Status: noncontrolled, OSHA: nonhazardous, TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing. DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): This product is listed on the DSL. Any impurities present in this product are exempt from listing. AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): This product is listed on AICS or otherwise complies with NICNAS. MITI (Japanese Handbook of Existing and New Chemical Substances): This product is listed in the Handbook or has been approved in Japan by new substance notification. ECL (Korean Toxic Substances Control Act): This product is listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act. Philippines Inventory (PICCS) : This product is listed on the Philippine Inventory or otherwise complies with PICCS. Inventory of Existing Chemical Substances in China: All components are listed on the Inventory of Existing Chemicals Substances in China (IECSC) or are covered under a polymer exemption.

Component CAS# 110-43-0:

On DSL and TSCA, EINECS, AICS, MITI and ECL lists.

Component 763-69-9:

Is on the TSCA EINECS and DSL Lists.

Component additive NJTSRN 800963-5023:

On TSCA List. Not a California Prop 65 chemical.

Component Polyester Polyol NJTSRNS0001C:

All components of this product are on the Canada DSL list and TSCA list.

Component Titanium Dioxide:

Contains Proposition 65 Chemicals, is on the PA Hazardous substance list, is on the NJ Right to Know Regulated chemical List. Titanium Dioxide is on inventory or in compliance with EINECS, TSCA, AICS, DSL, ENCS (JP), KECI (KR), PICCS (PH) and INV (CN).

Component Carbon:

Contains Proposition 65 Chemicals. Carbon: is listed on TSCA and DSL Canada.

Component acrylic polymers:

Listed on TSCA and DSL.

Component Barium Sulfate:

Listed on TSCA and DSL.

Component C.I. Pigment Violet 19 CAS# 1047-16-1:

Listed on TSCA and DSL.

Component Zinc Salt of Alkyl Naphalene Sulfonic Acid:

Listed on TSCA and DSL.

Component Solvent Naptha CAS# 64742-88-7:

Listed on TSCA and DSL.

Component Polyamine Polyester Polymer (non hazardous):

Listed on TSCA and DSL.

Component C.I. Pigment Blue 15 CAS# 147-14-8:

Listed on TSCA and DSL.

Component C.I. Pigment Blue CAS# 25869-00-5:

Listed on TSCA and DSL.

Component CAS# 164741-65-7:

Listed on TSCA and DSL.

Component C.I. Pigment Green 17 CAS# 1308-38-9:

Listed on TSCA and DSL.

Component Alkyl Polyether Phosphate Ester-trade secret:

Listed on TSCA and DSL

Component C.I. Pigment Green CAS# 1328-53-6:

Listed on TSCA and DSL.

Component C.I. Pigment Green 36 CAS# 14302-13-7:

Listed on TSCA and DSL.

Component CAS# 4531-49-1:

Listed on TSCA and DSL

Component CAS# 5567-15-7:

Listed on TSCA and DSL. Listed on the Pennsylvania, New Jersey Right to Know lists.

Component C.I. Pigment Yellow 42 CAS# 51274-00-1:

Listed on TSCA and DSL.

Component CAS# 15793-73-4:

Listed on TSCA and DSL. Listed on the Pennsylvania, New Jersey Right to Know lists.

Component C.I. Pigment Red 101 CAS# 1309-37-1:

Listed on TSCA and DSL.

Component C.I. Pigment Red 3 CAS# 2425-85-6:

Listed on TSCA and DSL.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component Aluminum Silicate Dehydrate CAS# 1332-58-7:

Listed on TSCA and DSL.

Component Mineral Spirits CAS# 8052-41-3:

Listed on TSCA and DSL.

Component C.I. Pigment Red 187 CAS# 59487-23-9:

Listed on TSCA and DSL.

Section 16 – Other Information

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

Revision Date: 04/15/15

Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

Product Name: Elite Chemical Resistant Urethane Coating (Colors) **PART B**
Product Codes: Series No. 8142-0400
Recommended Use: Concrete Coating.
Sold By: Gabriel First Corp.
Street Address: 233 West Commercial Street
City, State, Zip: East Rochester, NY 14445-0191
Telephone: 585-381-7000
Emergency Phone: 800-424-9300
Date Revised: 04-15-15
Chemical Name or Class: Isocyanate/Solvent Mixture

Section 2 – Hazards Identification

Hazard Overview

GHS Classification:

Flammable Liquid: Category 3
Specific Target Organ Toxicity Single Exposure: Category 3
Specific Target Organ Toxicity Following Repeated Exposure: Category 2
Respiratory Sensitization: Category 1B
Skin Corrosion/Irritation: Category 2
Skin Sensitizer: Category 1B
Serious Eye Irritation: Category 2B
Acute Toxicity Inhalation: Category 4
Acute Hazard to Aquatic Environment: Category 3
Chronic Hazards to Aquatic Environment: Category 3

GHS Label Elements and Precautionary Statements

Label Elements:



Hazard Statements:

Warning: Flammable liquid and vapor.
Warning: May cause respiratory irritation.
Warning: May cause damage to organs (auditory) through prolonged or repeated exposure.
Danger: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Warning: Causes skin irritation.
Warning: May cause an allergic skin reaction.
Warning: Causes serious eye irritation.
Warning: Harmful if inhaled.
Warning: Harmful to aquatic life.
Warning: Harmful to aquatic life with long lasting effects.

Precautionary Statements:

P102 Keep out of reach of children.
 P103 Read label before use.
 P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P271 Use only outdoors or in a well-ventilated area.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P284 Wear respiratory protection.
 P264 Wash hands thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Response:

P280 Wear protective gloves and clothing to prevent skin contact.
P273 Avoid release to the environment.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.
P370 + P378 In case of fire: Use Foam, alcohol foam, CO2, dry chemical for extinction.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 If inhaled, Call a POISON CENTER or doctor/physician if you feel unwell.
P314 Get medical advice/attention if you feel unwell.
P302 + P352 IF ON SKIN: wash with plenty of soap and water.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.
P361+P364 Take off immediately all contaminated clothing and wash it before reuse.
P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.
P342 + P311 IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician.
P333 + P313 IF SKIN irritation or rash occurs: Get medical advice/attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 IF eye irritation persists: Get medical advice/attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P233 Keep container tightly closed.

Disposal:

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.

HMIS Hazard Classification

Health: 2 Flammability: 3

Reactivity: 1 Personal Protective Equipment: G

Potential Health Effects

Eyes:

Can cause severe irritation, redness, tearing or blurred vision as well as corneal opacity and conjunctivitis.

Skin:

May cause irritation, defatting, and dermatitis.

Skin Absorption:

Can cause reddening, swelling, rash, scaling or blistering. Overexposure may cause sensitization resulting in reaction to contact of small amounts.

Ingestion:

Can cause gastrointestinal irritation, nausea, vomiting, diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Can cause corrosive action to mucous membranes and digestive tracts.

Inhalation Health Risks and Symptoms of Exposure:

Can cause nausea and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, and possible unconsciousness. Burning sensation to mucous membranes, shortness of breath and flu like symptoms may occur.

Health Hazards (Acute and Chronic):

Can cause sensitization by exposure through contact or high concentrations of vapor. Over-exposure to this material can cause cardiac abnormalities. Overexposure can possibly cause anemia. Liver abnormalities, kidney damage or eye damage. May cause asthma or other respiratory disorders, bronchitis, emphysema, hyperactivity and eczema.

Chronic Inhalation: as a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma), which will cause them to react to a later exposure to isocyanate at levels well below the TLV or MGL. These symptoms, which include chest tightness, wheezing, cough, shortness of breath or asthma attack, could be immediate or delayed up to several hours after exposure. Similar to many nonspecific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in several years. Chronic overexposure to isocyanates has been reported to cause lung damage, including decrease in lung function, which may be permanent. Sensitization may either be temporary or permanent.

Acute Skin Contact: Isocyanates react with the skin protein and moisture and can cause irritation. Symptoms of skin irritation may be reddening, swelling, rash, scaling, or blistering. Some persons may develop skin sensitization from skin contact. Cured material is difficult to remove.

Chronic Skin Contact: Prolonged contact with the isocyanate can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material or even as a result of vapor-only exposure.

Medical Conditions Generally Aggravated by Exposure:

Respiratory conditions or other allergic response.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity: OSHA: No NTP: No IARC: Yes
Product may contain Ethyl Benzene as a component of Xylene (IARC 2B).

Section 3 – Composition/Information on Ingredients

Ingredient	CAS No.	OSHA PEL	ACGIH TLV	OSHA STEL	Weight %
Hopolymer oOf HDI	28182-81-2	1 mg/m3	None	None	60-100
*Xylene	1330-20-7	100 ppm	100 ppm	150 ppm	12
*Ethyl Benzene (As a Component of Xylene)	100-41-4	100 ppm	100 ppm	125 ppm	<2%
N-Butyl Acetate	123-86-4	150 ppm	150 ppm	200 ppm	7-13
*Hexamethylene Diisocyanate (HDI)	822-06-0	None	.005 ppm	None	<1%

***Indicates toxic chemical (s) subject to the reporting requirements of Section 313 Title III and of 40 CFR 372.
 XYLENE ACGIH STEL= 150PPM.**

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

Section 4 – First Aid Measures

Eyes: Flush eyes with water for at least fifteen minutes and consult a physician.
Skin: For extreme exposure use a safety shower immediately. Wash affected area with soap and water and remove contaminated clothing promptly.
Ingestion: Do not induce vomiting. Keep person warm and consult a physician immediately. Give 1-2 cups of milk or water to drink.
Inhalation: Remove victim to fresh air area and administer oxygen if necessary. Obtain medical assistance, asthmatic type symptoms may occur immediately or be delayed for several hours. Treatment is symptomatic.

Section 5 – Fire-Fighting Measures

Flammable Limits in Air, (% by volume): **Upper:** Not available.
Lower: Not available.
Flash Point: 91F
Method Used: Seta Flash
Extinguishing Media: Foam, Alcohol Foam, CO2, Dry Chemical.
Special Fire Fighting Procedures: Do not enter confined fire area without full bunker gear including a positive pressure NIOSH approved self-contained breathing apparatus. Presence of solvents in product may require grounding. Remove all sources of ignition.
Unusual Fire and Explosion Hazards: If fire occurs, solvents may produce excessive pressure. Sealed drums may rupture and ignite. Vapors are heavier than air and may travel along the ground and ignite by any source of ignition. During a fire, HDI vapors and other toxic gasses may be evolved. Containers may burst if contaminated with water. Vapor flashback to source is possible.

Section 6 – Release Measures

Steps to be Taken in Case Material is Released or Spilled: Wear respirator and protective clothing. Remove all sources of ignitions. Remove excess with spark proof equipment, and the remainder with an absorbent such as clay and place in disposal containers. Contained air respirator may be necessary.

Section 7 – Handling and Storage

Precautions to be Taken in Handling and Storage: Store in cool dry place, seal all partially used containers. Wash with soap and water before eating, drinking, smoking, or using the toilet facilities. Mixed materials contain the hazards of all the components, therefore, read the SDS's of all the components prior to using material. Properly label all containers. Keep material away from all sources of ignition.
Other Precautions: Avoid all skin contact. Avoid breathing vapors generated from the material. Observe conditions of good general hygiene and safe working practices. Contaminated leather articles cannot be cleaned and must be discarded if contaminated with this product. Wash all contaminated clothing prior to the reuse thereof. Wear appropriate safety equipment and respirator at all times when ventilation is not sufficient to control vapors. Observe OSHA regulations for respirator use (29 CFR 1910.134). When spraying material avoid exposure to all mists generated by using air supplied respirator.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 8 – Exposure Controls/Personal Protection

Respiratory Protection:	Use a NIOSH approved respirator as required to prevent over-exposure to vapor in accordance with 29 CFR 1910.134. Engineering or administrative measures should be taken to reduce the risk and exposure. Use a positive pressure supplied air respirator when exceeding TLV's or if HDI Monomer concentrations exceed acceptable limits or when spraying material.
Ventilation:	Exhaust ventilation sufficient to keep airborne concentrations of HDI below their TLV and MGL maximum. Refer to Patty's Industrial Hygiene and Toxicology- Volume 1 (3 rd edition) Chapter 17 and Volume III (1 st edition) Chapter 3 for details.
Protective Gloves:	Impervious gloves – neoprene or rubber.
Eye Protection:	Splash goggles or glasses with side shields. Do not wear contact lenses when using this product.
Other Protective Clothing or Equipment:	Wear body covering clothing and other coverings as necessary such as an apron and appropriate footwear to avoid contact.
Work Hygienic Practices:	Observe good general hygienic practices.
See Section Three for occupational exposure limit values.	

Section 9 – Physical and Chemical Properties

Appearance and Odor:	Pale yellow liquids with solvent odor.
Boiling Point or Range:	279 ° F
Vapor Density (Air = 1):	Not available.
Specific Gravity (H₂O = 1):	1.1
Evaporation Rate:	Not available.
Solubility in Water:	Negligible.
Odor Threshold:	N/A
pH:	N/A
Melting Point/Freezing Point:	N/A
Vapor Pressure:	N/A
Auto-ignition Temperature:	N/A
Partition Coefficient: n-Octanol/water:	N/A
Decomposition Temperature:	N/A

Section 10 – Stability and Reactivity

Stability:	Stable.
Conditions to Avoid (Stability):	Avoid excessive heat or open flames as well as all sources of ignition such as sparks, heaters, static discharges, etc.
Incompatibility (Material to Avoid):	Avoid water, amines, strong bases, alcohols, metal compounds, and surface active compounds.
Hazardous Decomposition or By-Products:	May form toxic chemicals, carbon dioxide, carbon monoxide, oxides of nitrogen, HCN and HDI.
Hazardous Polymerization:	Moisture or materials that react with isocyanates and temperatures above 400 degrees F may cause polymerization.

Section 11 – Toxicological Information

Product:

Acute Oral Toxicity LD50 >5000 mg/kg (rat) (estimated value)
Acute Inhalation Toxicity LC50 390-453 mg/m³, 4h (rat)
Acute Dermal Toxicity LD50 >5000 mg/kg (rabbit)
Skin Irritation, rabbit, Draize, slightly irritating
Eye Irritation, rabbit, Draize, slightly irritating
Sensitization: Dermal – Sensitizer (Guinea Pig, Maximization Test). Dermal – Non-Sensitizer (Guinea Pig, Buehler).
Sensitization Inhalation – Non-sensitizer (Guinea Pig)
Repeated Dose Toxicity: 3 wks, inhalation NOAEL: 3.7-4.3 mg/m³ (rat)
Repeated Dose Toxicity: 90 d, inhalation NOAEL: 3.3-3.4 mg/m³ (rat)
Repeated Dose toxicity: Irritation to lungs and nasal cavity.
Mutagenicity: Genetic Toxicity in Vitro, Ames: negative (salmonell typhimurium, Metabolic Activation: with/without).

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

COMPONENT n-Butyl Acetate:

Acute oral LD50 > 5000 mg/kg (rat), Acute Inhalation Toxicity: LC50 > 23.4 mg/l, 4hh (rat), Acute Dermal Toxicity LD50 > 5000 mg/kg (rabbit), Skin Irritation Guinea pig Acute Dermal Irritation exposure time 24h – Non-irritating, Skin Irritation Human patch test exposure time 48h – Non-irritating, Eye Irritation rabbit Draize exposure time 24h – slightly irritating, Sensitization dermal – non-sensitizing (guinea pig, human – maximization test). Repeated Dose Toxicity – 13 weeks inhalation NOAEL: 500 ppm (rat). Mutagenicity Genetic Toxicity in Vitro: Ames negative (Salmonella typhimurium, Metabolic Activation: with/without).

COMPONENT Xylene:

Inhalation LC50 26800ppm, Skin LD50 2000 mg/kg, Ingestion LD50 4.3 g/kg. Exposure may effect skin, eye, liver, kidney, nervous system, respiratory system and lungs. High concentrations may lead to nervous system effects. Repeated overexposure has produced toxic effects in developing and young laboratory animals. Aspiration into lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal. Xylene may contain Ethyl Benzene.. Ethyl Benzene has shown limited evidence of a carcinogenic effect.

COMPONENT Ethyl Benzene:

Acute Oral toxicity LD50: ca. 3500 mg/kg (rat); Acute inhalation LC50: 17.2 mg/l 4h (rat); Acute Dermal Toxicity: 17,800 mg/kg (rabbit); Skin Irritation rabbit Draize exposure time 24h – slightly irritating. Eye Irritation rabbit Draize – severely irritating. Sensitization dermal (human patch test) non-sensitizer. Repeated Dose toxicity 28 days inhalation NOAEL: 3.4 mg/l (rabbit). Mutagenicity Genetic Toxicity in Vitro: Ames: Negative (salmonella typhimurium, metabolic activation with/without). Carcinogenicity: Ethyl benzene was tested by inhalation exposure in mice and rats. In mice, there was an increased incidence of lung adenomas in males and liver adenomas in females. In male rats, there was an increased incidence of renal tubule adenomas and carcinomas. Two Studies of workers potentially exposed to ethyl benzene in a production plant and a styrene polymerization plant, showed no excess cancer incidence and no excess cancer mortality during a 15 year follow-up. Toxicity to Reproduction/Fertility: Inhalation (monkey, male) Reproductive effects have been observed in animal studies. In a generation study, inhalation (rat/female) NOAEL (parental): 100ppm NOAEL (F2): 100ppm. Developmental Toxicity/Teratogenicity rat, female, inhalation, gestation, daily, NOAEL (teratogenicity): 100ppm (maternal): 100ppm. Tratogenetic effects seen only with maternal toxicity., Fetotoxicity seen only with maternal toxicity. Rabbit, female, inhalation, gestation, daily, NOAEL (teratogenicity) < 1000 mg/m3, NOAEL (maternal) < 1000 mg/m3.

Section 12 – Ecological Information**COMPONENT Homopolymer of HDI:**

Biodegradation: 0%, Exposure time: 28 days, not readily biodegradable. Acute and Prolonged Toxicity to fish LC0 > 100 mg/l (zebra fish, 96 h). Acute toxicity to aquatic invertebrates: EC0 > 100 mg/l (water flea, 48 h). Toxicity to aquatic plants EC50 > 1000 mg/l (green algae, 72 h). Toxicity to Microorganisms: EC50 > 1000 mg/l (activated sludge microorganisms, 3 h).

COMPONENT n-Butyl Acetate:

Biodegradation: aerobic, 98%, exposure time 28 days. Biochemical oxygen demand (BOD) 1020 mg/g. Chemical Oxygen demand (COD) 2,320 mg/g. Bioaccumulation: ca. 4-14 BCF. Acute and Prolonged Toxicity to Fish LC50: 18 mg/l (fathead Minnow, 96 h). Acute Toxicity to Aquatic Invertebrate EC50: 72.8 mg/l (water flea, 48 h). Toxicity to aquatic plants EC50: 670 mg/l, end point: growth (Cryptomonad, 48 h). Toxicity to Microorganisms EC50: 959 mg/l (Pseudomonas putida, 48 h).

COMPONENT Xylene:

Acute Toxicity: Fish: Toxic 1 < LCECIC50 < 10mg/l, Aquatic Invertebrates: Toxic 1 < LC/EC/IC50 <10mg/l, Algae: Toxic 1 < LC/EC/IC50 <10 mg/l. Mobility – floats on water. If it enters the soil it will be highly mobile and may contaminate groundwater. Oxidises rapidly by photo-chemical reactions in air.

COMPONENT Ethyl Benzene:

Biodegradation, Aerobic, 50%, Exposure time 28 days. Biochemical Oxygen demand (BOD) 5 days, 2.8% and 35 days, 1780 mg/g. Bioaccumulation: Cyprinus carpio (Carp), 15 BCF. Acute and Prolonged Toxicity to Fish LC50: 12.1 mg/l (fathead minnow, 96 h). Acute Toxicity to Aquatic Invertebrates EC50: 1.8-2.9 mg/l (water flea, 48 h). Toxicity to Aquatic Plants EC50: 4.6 mg/l (green algae, 72 h). Toxicity to microorganisms EC50: 130 mg/l (activated sludge microorganisms, 48 hr).

Section 13 – Waste Disposal**Waste Disposal Method:**

Dispose of the material in a waste disposal site in accordance with local, state, and federal laws.

Section 14 – Transport Information**DOT:**

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III

IMO/IMDG:

UN1993, FLAMMABLE LIQUID N.O.S. (CONTAINS XYLENE, BUTYL ACETATE), 3, PG III

Section 15 – Regulatory Information**Product:**

OSHA HAZCOM STANDARD RATING: Hazardous. All components on TSCA
Massachusetts, New York, Pennsylvania Right to Know list includes the following components: Homopolymer of HDI CAS# 28182-81-2 @ 60-100%; n-Butyl Acetate CAS# 123-86-4 @ 10-20%; Xylene CAS# 1330-20-7 @ 7-13%; Ethyl Benzene CAS# 100-41-4 @ 1-5%.
Massachusetts, New York, Pennsylvania Special hazardous Substance includes the following components: n-Butyl Acetate CAS# 123-86-4 @ 10-20%; Xylene CAS# 1330-20-7 @ 7-13%; Ethyl Benzene CAS# 100-41-4 @ 1-5%; Hexamethylene Diisocyanate (HDI) CAS# 822-06-0 @ <0.6%.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

California Prop 65: This product contains chemicals known to the State of California to be carcinogenic: Ethyl Benzene CAS# 100-41-4 @ 1-5%.
US EPA CERCLA Hazardous Substances (40 CFR 302): n-butyl acetate reportable quantity 5000 lbs.
US EPA CERCLA Hazardous Substances (40 CFR 302): Xylene reportable quantity 100 lbs.
US EPA CERCLA Hazardous Substances (40 CFR 302): Ethyl Benzene reportable quantity 1000 lbs.
US EPA Emergency Planning and Community Right to Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.5) components, Xylene and Ethyl Benzene.

Section 16 - Other Information

DISCLAIMER: The information Contained herein is based on the data available and is believed to be accurate, However, the manufacturer makes no warranty expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Accordingly, we assume no responsibility for injury from the use of this product.

N/A = Not Available

Revision Date: 04/15/15