

SAFETY DATA SHEET

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision Date: 01-10-2015

Section 1 – Identification of the Substance/Mixture and of the Company/Undertaking

1.1 – Product Identifier

Product Number: 2660-0953
 Product Identifier: **Fast-1-2-3 Spray 'N Wipe Cleaner**
 Revision Date: 01-10-2015

1.2 – Details of the Supplier of the Safety Data Sheet

Manufactured For: Gabriel First Corp.
 233 W. Commercial Street
 East Rochester, NY 14445 USA
 Telephone: 585-381-7000

1.3 – Emergency Telephone Number

Emergency Telephone: 800-424-9300

1.4 – Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use: Cleaner
 Recommended Restrictions: None known

Section 2 – Hazard's Identification

2.1 – Classification of the Substance or Mixture

Physical Hazards: Gases under pressure. Liquefied gas
 Health Hazards: Serious eye damage/eye irritation. Category 2A
 Environmental Hazards: Not classified.
 OSHA Defined Hazards: Not classified.

2.2 – Label Elements

Label Elements:



Signal Word: Warning.
 Hazard Statement: Contains gas under pressure; may explode if heated. Causes serious eye irritation.
 Precautionary Statement
 Prevention: Wash thoroughly after handling. Wear eye/face protection.
 Response: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 Storage: Protect from sunlight. Store in a well-ventilated place.
 Disposal: Dispose of waste and residues in accordance with local authority requirements.

2.3 – Other Hazards

Hazard(s) Not Otherwise Classified (HNOC): Not known.
 Supplemental Information: None.

Section 3 – Composition/Information on Ingredients

3.1 – Mixtures

Chemical Name	Common Name and Synonyms	CAS Number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Butane		106-97-8	1 - 2.5
EDTA Tetrasodium Salt		64-02-8	1 - 2.5
Other components below reportable levels			90 - 100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 4 – First Aid Measures**4.1 – Description of First Aid Measures**

First Aid Measures After Inhalation:	Move to fresh air. Call a physician if symptoms develop or persist.
First Aid Measures After Skin Contact:	Wash off with soap and water. Get medical attention if irritation develops and persists.
First Aid Measures After Eye Contact:	Rinse with water. Get medical attention if irritation develops and persists.
First Aid Measures After Ingestion:	Rinse mouth. Get medical attention if symptoms occur.

4.2 – Most Important Symptoms/Effects, Acute and Delayed

Most Important Symptoms/Effects, Acute and Delayed:	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
--	---

4.3 – Indication of Immediate Medical Attention and Special Treatment Needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

4.4 – General Information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Section 5 – Fire-Fighting Measures**5.1 – Extinguishing Media**

Suitable Extinguishing Media:	Water fog. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable Extinguishing Media:	None known

5.2 – Special Hazards Arising From the Substance or Mixture

Specific Hazards Arising From the Chemical:	Contents under pressure.
--	--------------------------

5.3 – Advice for Firefighters

Special Protective Equipment and Precautions for Firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
--	---

Fire-Fighting Equipment/Instructions:	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
--	---

Specific Methods:	Use standard firefighting procedures and consider the hazards of other involved materials.
--------------------------	--

Section 6 – Accidental Release Measures**6.1 – Personal Precautions, Protective Equipment and Emergency Procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2 – Methods and Material for Containment and Cleaning Up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

6.3 – Environmental Precautions

Avoid discharge into drains, water courses or onto the ground.

Section 7 – Handling and Storage**7.1 – Precautions for Safe Handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2 – Conditions for Safe Storage, Including Any Incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Section 8 – Exposure Controls/Personal Protection

8.1 – Control Parameters

Occupational Exposure Limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)				
Components		Type		Value
2-Butoxyethanol (CAS 111-76-2)		PEL		240 mg/m ³ 50 ppm
US. ACGIH Threshold Limit Values				
Components		Type		Value
2-Butoxyethanol (CAS 111-76-2)		TWA		20 ppm
Butane (CAS 106-97-8)		STEL		1000 ppm
US. NIOSH: Pocket Guide to Chemical Hazards				
Components		Type		Value
2-Butoxyethanol (CAS 111-76-2)		TWA		24 mg/m ³ 5 ppm
Butane (CAS 106-97-8)		TWA		1900 mg/m ³ 800 ppm
Biological Limit Values ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in Urine	*

* - For sampling details, please see the source document.

8.2 – Exposure Guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2)

Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate Engineering Controls:

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual Protection Measures, Such As Personal Protective Equipment:

Eye/face Protection:

If contact is likely, safety glasses with side shields are recommended.

Hand Protection:

For prolonged or repeated skin contact use suitable protective gloves.

Skin Protection

Other:

Wear suitable protective clothing.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal Hazards:

Wear appropriate thermal protective clothing, when necessary.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

General Hygiene Considerations:

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Section 9 – Physical and Chemical Properties**9.1 – Information on Basic Physical and Chemical Properties****Appearance**

Physical State:	Gas.
Form:	Aerosol. Liquefied gas.
Color:	Not available.
Odor:	Pleasant.
Odor Threshold:	Not available.
pH:	Not available.
Melting Point/Freezing Point	Not available.
Initial Boiling Point and Boiling Range:	212 °F (100 °C) estimated
Flash Point:	-156.0 °F (-104.4 °C) Propellant estimated.
Evaporation Rate:	Not available.
Flammability (solid, gas):	Not available.
Upper/Lower Flammability or Explosive Limits	
Flammability Limit – Lower (%):	Not available.
Flammability Limit – Upper (%):	Not available.
Explosive Limit - Lower (%):	Not available.
Explosive Limit - Upper (%):	Not available.
Vapor Pressure:	60 - 75 psig @70F estimated.
Vapor Density:	Not available.
Relative Density:	Not available.
Solubility(ies)	
Solubility (water):	Not available.
Partition Coefficient (n-octanol/water):	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Other Information	
Flame Extension:	0 in estimated
Specific Gravity:	0.922 estimated

Section 10 – Stability and Reactivity**10.1 – Reactivity**

Reactivity:	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	Hazardous polymerization does not occur.
Incompatible Materials:	Strong oxidizing agents.
Conditions to Avoid:	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Hazardous Decomposition Products:	No hazardous decomposition products are known.

Section 11 – Toxicological Information**11.1 – Information on Likely Routes of Exposure**

Ingestion:	Expected to be a low ingestion hazard.
Inhalation:	Prolonged inhalation may be harmful.
Skin Contact:	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye Contact:	Causes serious eye irritation.
Symptoms Related to the Physical, Chemical and Toxicological Characteristics:	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

11.2 – Information on Toxicological Effects

Acute Toxicity

Components	Species	Test Results	
2-Butoxyethanol (CAS 111-76-2)			
Acute <i>Dermal</i> LD50	Guinea pig	230 ml/kg, 24 Hours 7.3 ml/kg, 4 Days	
	Rabbit	450 ml/kg, 24 Hours 435 mg/kg, 24 Hours 0.63 ml/kg	
	Rat	> 2000 mg/kg, 24 Hours	
	<i>Inhalation</i> LC50	Rabbit	400 ppm, 7 Hours
		Rat	450 ppm, 4 Hours
	<i>Oral</i> LD100	Rabbit	695 mg/kg
		Dog	> 695 mg/kg
		Guinea pig	1200 mg/kg
	LD50	Rat	530 - 2800 mg/kg

Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results
EDTA Tertrasodium Salt (CAS 64-02-8)		
Acute <i>Oral</i> LD50	Rat	1658 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin Corrosion/Irritation:	Prolonged skin contact may cause temporary irritation.
Serious Eye Damage/Eye Irritation:	Causes serious eye irritation.
Respiratory or Skin Sensitization	
Respiratory Sensitization:	Not available.
Skin Sensitization:	This product is not expected to cause skin sensitization.
Germ Cell Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity:	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
2-Butoxyethanol (CAS 111-76-2)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not listed.	
Reproductive Toxicity	This product is not expected to cause reproductive or developmental effects.
Specific Target Organ Toxicity – Single Exposure:	Not applicable.
Specific Target Organ Toxicity – Repeated Exposure:	Not classified.
Aspiration Hazard:	Not likely, due to the form of the product.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Chronic Effects: Prolonged inhalation may be harmful. May be harmful if absorbed through skin.
2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Section 12 – Ecological Information

12.1 – Ecotoxicity

Ecotoxicity: Harmful to aquatic life.

Product		Species	Test Results
Fast-1-2-3 Spray & Wipe Cleaner (CAS Mixture)			
Aquatic			
Algae	IC50	Algae	88.1875 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia	33640.2813 mg/L, 48 Hours, estimated
Fish	LC50	Fish	1174.3357 mg/L, 96 Hours estimated

Components		Species	Test Results
2-Butoxyethanol (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (<i>Menidia beryllina</i>)	1250 mg/l, 96 hours

EDTA Tetrasodium Salt (CAS 64-02-8)		Species	Test Results
Aquatic			
Algae	IC50	Algae	1.01 mg/L, 72 Hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>)	472 - 500 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

12.2 – Persistence and Degradability

No data is available on the degradability of this product.

12.3 – Bioaccumulative Potential

No data available.

Partition coefficient n-octanol / water (log Kow)	
2-Butoxyethanol	0.83
Butane	2.89

12.4 – Mobility in Soil

No data available.

Other Adverse Effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Section 13 – Disposal Considerations

13.1 – Waste Treatment Methods

Disposal Instructions: Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local Disposal Regulations: Dispose in accordance with all applicable regulations.

Hazardous Waste Code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from Residues / Unused Products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 14 – Transport Information**DOT**

UN Number:	UN1950
UN Proper Shipping Name:	Aerosols.
Transport Hazard Class(es)	
Class:	2.2
Subsidiary Risk:	-
Label(s):	2.2
Packing Group:	Not applicable.
Special Precautions For User:	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions:	306
Packaging Non Bulk:	None
Packaging Bulk:	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN Number:	UN1950
UN Proper Shipping Name:	Aerosols, non-flammable.
Transport Hazard Class(es)	
Class:	2.2
Subsidiary Risk:	-
Label(s):	2.2
Packing Group:	Not applicable.
Environmental Hazards:	No
ERG Code:	2L
Special Precautions for User:	Read safety instructions, SDS and emergency procedures before handling.
Other Information	
Passenger and Cargo Aircraft:	Allowed.
Cargo Aircraft Only:	Allowed.
Packaging Exceptions:	LTD QTY

IMDG

UN Number:	UN1950
UN Proper Shipping Name:	AEROSOLS
Transport Hazard Class(es)	
Class:	2.2
Subsidiary Risk:	-
Label(s):	2.2
Packing Group:	Not applicable.
Environmental Hazards:	
Marine Pollutant:	No.
EmS:	Not available.
Special Precautions For User:	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions:	LTD QTY

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT



IATA; IMDG



Section 15 – Regulatory Information

15.1 – US Federal Regulations

US Federal Regulations:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency Release Notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories:

Immediate Hazard - Yes

Delayed Hazard - No

Fire Hazard - No

Pressure Hazard - Yes

Reactivity Hazard - No

SARA 302 Extremely Hazardous Substance

Chemical Name	CAS Number	Reportable Quantity	Threshold Planning Quantity	Threshold Planning Quantity, Lower Value	Threshold Planning Quantity, Upper Value
Anhydrous Ammonia	7664-41-7	100	500 lbs		
Benzyl Chloride	100-44-7	100	500 lbs		
Hydrogen Peroxide	7722-84-1	1000	1000 lbs		

SARA 311/312 Hazardous Chemical:

No

SARA 313 (TRI Reporting)

Not regulated.

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)

Safe Drinking Water Act (SDWA):

Not regulated.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2 – US State Regulations

US. Massachusetts RTK – Substance List

2-Butoxyethanol (CAS 111-76-2)
Butane (CAS 106-97-8)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2)
Butane (CAS 106-97-8)

US. Pennsylvania Worker and Community Right-to-know Law

2-Butoxyethanol (CAS 111-76-2)
Butane (CAS 106-97-8)

US. Rhode Island RTK

Butane (CAS 106-97-8)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzyl chloride (CAS 100-44-7) Listed: January 1, 1990

15.3 – International Inventories

Country(s) or Region	Inventory Name	On Inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Section 16 – Other Information

Revision Date: 01-10-2015

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.